

Data Sheet

Reference No.: 42594

Fine Blanking Press -mechanical-

Brand: FEINTOOL
 Model: GKP F 40
 YoM, approx.: 1981 used
 Reconditioned: 2022
 Controls:



Slide

total force (nominal): 40 to
 stroke: 45 mm
 stroke rate (max.): 110 /min

V-Ring

nominal force: 12 to
 stroke: 8 mm

Tool Dimensions

lower table (left-right): 300 mm
 lower table (front-back): 300 mm
 upper table (left-right): 280 mm
 upper table (front-back): 380 mm
 shut height max.: 195 mm
 distance between columns (H-frame): 320 mm
 passline opening (free passage in side columns): 160 mm

Strip-Feeder

sheet width max.: 100 mm
 sheet thickness max.: 4 mm
 feeding step min.: 0 mm
 feeding step max.: 60 mm
 sheet length min.: 980 mm
 nominal force: 0.4 kN

Electrical specifications

total power consumption: 6 kW
 mains frequency: 50 Hz

Dimensions / weights

space requirements -left/right-: 2063 mm
 space requirements -front/back-: 1350 mm
 total height: 1800 mm
 total weight approx.: 2500 kg

Attachments -Fineblanking Press-

European CE standards: yes

Seller:

Post-Venta Carreras S.A.
 Eduard Peña
 Pol. Ind. Els Plans d'Arau C/ Nicolau Copèrnic, 2, 08787
 La Pobla de Claramunt, Spain
 +34 938 088 099
 edu@prodeq.es