

Data Sheet

Reference No.: 50568

CNC lathe

Brand: INDEX
Model: C 65
YoM, approx.: 2007 used
Reconditioned:
Controls: CNC controls SIEMENS 840 D POWER LINE



basic functions

number of spindles:	2
number of turrets:	3
live positions: yes	
number of c-axes:	2
number of y-axes:	3
number of b-axes:	3

Working Range Turning

turning diameter (max):	140 mm
bar diameter (max):	65 mm
workpiece length max.:	600 mm

main spindle

spindle revolutions (min):	1 /min
spindle revolutions (max):	5000 /min

counter spindle

spindle revolutions (min):	1 /min
spindle revolutions (max):	5000 /min
Z-axis travel:	600 mm

X/Z slide

Z-axis travel:	360 mm
X-axis travel:	110 mm
Y-axis travel:	70 mm
rotating range B-axis up to:	1 °
rapid traverse Z:	45 mm/min
rapid traverse X:	25 mm/min
rapid traverse Y:	12 mm/min
number of tool positions (total):	36
number of live positions:	36
- rotation speeds (max):	6000 /min

Electrical specifications

mains power supply:	72 kVA
mains voltage:	400 V
mains frequency:	50 Hz

Dimensions / weights

space requirements -left/right-:	6100 mm
space requirements -front/back-:	1690 mm
total height:	2810 mm
total weight approx.:	6500 kg

attachments (turning)

chip conveyor: yes
through spindle coolant
attachment: yes
European CE standards: yes

Additional Information:

Including bar loader, Profimat 65.8*270/8 year 2005
loading length 500-3000mm. Spindeleinsatzrohren
16,25,30,40,45,55,60,65mm (multi-channel loading
magazine) Including chip conveyor

Chucks and tools are not included in the scope of
delivery.

Seller:

ProdEq Trading GmbH
Daniel Groetzinger
Reckholder 1, 9527 Niederhelfenschwil, Switzerland
+41 71 948 70 60
daniel.groetzinger@prodeq.ch

Photos & Documents

Reference No.: 50568

