

Data Sheet

Reference No.:51703

Turning and Milling Center

Brand: OKUMA
Model: MULTUS U4000
YoM, approx.: 2016 used
Reconditioned:
Controls: CNC controls OKUMA OSP P300S



basic functions

number of spindles:	2
number of turrets:	1
live positions: yes	
number of c-axes:	2
number of b-axes:	1

spindle / head

- positioning/indexing:	0.001 °
spindle revolutions (max):	12000 /min
tool fixture: HSK A63	
drive power:	22 kW

Working Range Turning

turning diameter (max):	650 mm
bar diameter (max):	95 mm

main spindle

spindle revolutions (max):	3000 /min
drive power:	32 kW
spindle torque:	955 Nm
spindle diameter:	112 mm
spindle bore diameter:	95 mm

counter spindle

spindle revolutions (max):	4000 /min
drive power:	26 kW
spindle torque:	420 Nm

X/Z slide

Z-axis travel:	1600 mm
X-axis travel:	695 mm
Y-axis travel:	300 mm
rotating range B-axis up to:	210 °
number of tool positions (total):	12

Tool magazine

number of positions:	80
tool diameter max.:	90 mm
- with free neighbour positions:	130 mm
tool length max.:	400 mm

Electrical specifications

mains voltage:	400 V
mains frequency:	50 Hz

Dimensions / weights

space requirements -left/right-:	4480 mm
total height:	3030 mm
total weight approx.:	18000 kg

attachments (turning)

chip conveyor: yes
hydraulic system: yes
European CE standards: yes

Seller:

ProdEq Trading GmbH
Emanuel Unger
Reckholder 1, 9527 Niederhelfenschwil, Switzerland
+41 71 948 70 60
emanuel.unger@prodeq.ch

Photos & Documents

Reference No.: 51703

