

Data Sheet

Reference No.: 52869

Milling Machine (floor type)

Brand: ANAYAK
Model: HVM 5000 P
YoM, approx.: 2005 used
Reconditioned:
Controls: CNC controls HEIDENHAIN ITNC 530



Working Range -cubic-

number of processing axes (excl parallel axes):	5
X-axis travel:	5000 mm
Y-axis travel:	1500 mm
Z-axis travel:	1050 mm
rotating range A-axis from:	-225 °
rotating range A-axis up to:	45 °
rotating range B-axis from:	-180 °
rotating range B-axis up to:	165 °
rotating range C-axis from:	360 °
rotating range C-axis up to:	360 °

Table

table surface (left-right):	3410 mm
table surface (front-back):	1000 mm
workpiece load (max):	5000 kg

Floor Plate

table surface (left-right):	3410 mm
table surface (front-back):	1000 mm

spindle / head

spindle revolutions (min):	60 /min
spindle revolutions (max):	5000 /min
tool fixture: ISO SK 50	

Axis drives

traverse velocity X (max):	10000 mm/min
traverse velocity Y (max):	10000 mm/min
traverse velocity Z (max):	6000 mm/min
rapid traverse X:	22500 mm/min
rapid traverse Y:	20000 mm/min
rapid traverse Z:	10000 mm/min

Dimensions / weights

total weight approx.:	43500 kg
-----------------------	----------

attachments

chip conveyor: yes

Additional Information:

1 rotary table (360°) 1000 x 1000 mm, load 5000 kg
40 tool places Tool dimensions: Diameter of the neighbouring free spaces 200 mm Diameter of the neighbouring occupied spaces 125 mm Max. Max. length 400 mm Max. Max. weight 25 kg Hydraulic unit: 28 L/min Chip conveyor Workpiece measuring system: Radio measuring system TS460 Heidenhain Spindle hours: 16,966 h IKZ: 26L/min 22bar Cooling unit MSF31.8 /2P (for cooling head oil) Machine is in very good operating condition.

Seller:

ProdEq Trading GmbH
Emanuel Unger
Reckholder 1, 9527 Niederhelfenschwil, Switzerland
+41 71 948 70 60
emanuel.unger@prodeq.ch

Photos & Documents

Reference No.: 52869

