

Data Sheet

Reference No.: 54093

Cylindrical Grinder - External

Brand: ROWEIG
Model: SA6 S/U - FMNC
YoM, approx.: 2002 used
Reconditioned:
Controls:



Working Range Cylindrical Grinding

swing diameter (max): 515 mm
workpiece weight between centers (max): 500 kg
workpiece weight flying (max): 120 kg

Working Range External Grinding

grinding diameter (max): 515 mm
grinding length: 1500 mm

Table -cylindrical grinding-

tilting range (B-direction) min: 8.3 °
rotating range B-axis up to: -4 °
longitudinal travel: 1680 mm

Workpiece Spindlestock

spindle revolutions (min): 14 /min
spindle revolutions (max): 114 /min
number of gears: 2
drive power: 1.5 kW
tool fixture: MK 6

tailstock

sleeve stroke: 40 mm
taper: MK 5

Spindlestock Grinding Spindle

tilting range (B-direction) min: -10 °
rotating range B-axis up to: 10 °
drive power: 15 kW

Grinding Tool

type of grinding tool: wheel
diameter (max): 630 mm
borehole: diameter: 203.2 mm
width: 125 mm

Dimensions / weights

space requirements -left/right-: 5150 mm
space requirements -front/back-: 3700 mm
total height: 2200 mm
total weight approx.: 6500 kg

attachments (grinding)

self-centering chuck: 1
coolant unit: yes

Seller:

ProdEq Deutschland GmbH Standort Hückeswagen
Thomas Berger
Weberweg 2, 42499 Hückeswagen, Germany
+49 2192 935 382
thomas.berger@prodeq.de

Photos & Documents

Reference No.: 54093

