

Características técnicas:

Nº de referencia 55511

Additive Manufacturing System

Marca: SLM
Modelo: 280 2.0 SINGLE 700W
Año de fabricación: 2022 used
Reconstruida:
Control: Control CNC SLM



Datos de conexión eléctricos

Tensión de conexión: 400 V
Frecuencia de la red: 50 Hz

Dimensiones / peso

espacio requerido -
izquierdo/derecha-: 2600 mm
espacio requerido -delante/atrás-: 1200 mm
Altura total: 2700 mm

Información adicional:

Machines in excellent condition serviced annually by the manufacturer (service reports available).

... Accessories:

- HRS050 L/W cooling package,
- PSM100 V3 sieving station,
- BPH280 handling unit and bottle lift,
- Material change kit,
- SLM280 2.0 complete including PSM100,
- Powder hopper,
- Substrate plates (1.2709 & AlSi10Mg),
- Additional filter housings and filter elements, etc.

Build volume: 280 x 280 x 365 mm minus substrate plate height

Machine configuration: Single optic, 1 x 700W

Build rate: up to 113 cm³/h (material dependent)

Laser lifespan: 1500 h

Variable layer thickness: 20 µm - 90 µm

Min. feature size: 150 µm

Focus diameter: 80 - 115 µm

Max. scan speed: 10 m/s

Average protective gas consumption during the build process: 5.0 l/min (argon)

Average protective gas consumption during the flooding process: 110 l/min (argon)

Vendedor:

ProdEq Trading GmbH
Michael Weishaupt
Reckholder 1, 9527 Niederhelfenschwil, St
+41 71 948 70 60
michael.weishaupt@prodeq.ch

Fotos y documentos

Nº de referencia 55511

