

Data Sheet

Reference No.: 43494

Станок для литья пластмассы под давлением

Brand: BATTENFELD
Model: HM 160/525
YoM, approx.: 2007 used
Reconditioned:
Controls: контроль ЧПУ типа CNC UNILOG B6



Mould clamping unit

locking force:	160 to
die opening stroke max.:	650 mm
mould height min.:	300 mm
mould height max.:	950 mm
max. distance between tool-plates:	950 mm
space between tie bars L1:	570 mm
space between tie bars L2:	520 mm

Injection Unit

Diameter of screw:	40 mm
Injection pressure:	2100 bar
Shot volume:	251 cm ³
Shot weight max. (Polystyrol):	228 g

Hydraulic unit

oil volume:	400 ltr
-------------	---------

Данные электр. Подключения

Напряжение питания:	400 V
Частота тока в сети:	50 Hz

Габариты / вес

Требуемая площадь (длина):	5000 mm
Требуемая площадь (ширина):	1650 mm
Общая высота:	2140 mm
Общий вес (около):	7300 kg

Additional Information:

Machine in very good condition (= photo) Operating hours 12`800h Equipment: - 4 temperature control points for hot runner - granulate dryer - conveyor belt - temperature control unit - Waste chipper

Seller:

ProdEq Trading GmbH
Michael Weishaupt
Reckholder 1, 9527 Niederhelfenschwil, Switzerland
+41 71 948 70 60
michael.weishaupt@prodeq.ch

Photos & Documents

Reference No.: 43494



Screen

