

Data Sheet

Reference No.: 45513

Станки для размотки и выпрямления проволоки из катушек

Brand: HS AUTOMATION
Model: MS410L
YoM, approx.: 2015 used
Reconditioned:
Controls:



Overall Specifications (coil lines)

sheet width max.: 500 mm
coil weight max.: 4 to

Coil Chair

coil weight max.: 4 to
Ход: 540 mm
movement: 1700 mm

Decoiler

design: single reel
max. diameter of coil: 1900 mm
mandrel expansion range from: 450 mm
mandrel expansion range up to: 550 mm
feed velocity max.: 30 m/min

Данные электр. Подключения

Напряжение питания: 400 V
Частота тока в сети: 50 Hz

Additional Information:

- Hydraulic spreading process - Reel drive three-phase motor - Tape loop control Pull-off via preset pressure or via loop control - Coil stop arms 6 pieces with quick clamping system - Protective device against the belt from hitting the coil - Pneumatic pressure arm - 4 tonne coil turning lifting device with reel travelling gear, hydraulically controlled

Seller:

Post-Venta Carreras S.A.
Antonio Vega
Pol. Ind. Els Plans d'Arau C/ Nicolau Copèrnic, 2, 08787
La Pobla de Claramunt, Spain
+34 938 088 099
antonio@prodeq.es

Photos & Documents

Reference No.: 45513

