

## Data Sheet

Reference No.: 51667

## obradni centar za struganje i glodanje

Brand: DOOSAN  
Model: PUMA 2600 ST  
YoM, approx.: 2012 used  
Reconditioned:  
Controls: CNC upravljanje FANUC 31I A



### Working Range Turning

turning diameter (max): 760 mm  
bar diameter (max): 46 mm  
workpiece length max.: 1540 mm

### main spindle

spindle revolutions (max): 4000 /min  
snaga motora: 22 kW  
c-axis: yes

### counter spindle

spindle revolutions (max): 4000 /min  
snaga motora: 26 kW  
c-axis: yes

### X/Z slide

Z-axis travel: 1585 mm  
X-axis travel: 630 mm  
Y-axis travel: 230 mm  
number of tool positions (total): 12  
number of live positions: 12  
- rotation speeds (max): 4000 /min

### X/Z slide

rotating range B-axis up to: 0.001 °  
traverse velocity Z (max): 1515 mm/min  
traverse velocity X (max): 220 mm/min  
- rotation speeds (max): 12000 /min  
- drive power: 22 kW

### Tool magazine

number of positions: 40  
tool diameter max.: 90 mm  
- with free neighbour positions: 130 mm  
tool length max.: 400 mm

### Electrical specifications

mains voltage: 400 V  
mains frequency: 50 Hz

### Dimensions / weights

space requirements -left/right-: 5125 mm  
space requirements -front/back-: 2625 mm  
total height: 3052 mm  
total weight approx.: 1550 kg

### attachments (turning)

chip conveyor: yes  
coolant unit: yes  
coolant through turret: yes  
through spindle coolant  
attachment: yes  
hydraulic system: yes  
European CE standards: yes

### Additional Information:

Switch-on hours :41000h Running time:19000h  
Milling:3400H

### Seller:

ProdEq Trading GmbH  
Emanuel Unger  
Reckholder 1, 9527 Niederhelfenschwil, Switzerland  
+41 71 948 70 60  
emanuel.unger@prodeq.ch

## Photos & Documents

Reference No.: 51667

