

Data Sheet

Reference No.:56380

koordinatna brusilica

Brand: HAUSER
 Model: S40-400 S
 YoM, approx.: 1996 used
 Reconditioned:
 Controls: CNC upravljanje FANUC 0 M



Working Range -cubic-

X-axis travel: 650 mm
 Y-axis travel: 450 mm
 Z-axis travel: 130 mm

Table

table surface (left-right): 770 mm
 table surface (front-back): 630 mm
 workpiece load (max): 500 kg

spindle / head

spindle revolutions (min): 9000 /min
 spindle revolutions (max): 60000 /min

Electrical specifications

mains voltage: 400 V
 mains frequency: 50 Hz

Dimensions / weights

space requirements -left/right-: 5400 mm
 space requirements -front/back-: 4000 mm
 total weight approx.: 4550 kg

Additional Information:

work area protection
 -exhaust system with electrostatic air filter
 -fire protection system (to be assessed by a qualified body)
 -HTG-RWS-60 automatic belt filter cooling unit
 x1 MSS (Multi-Sensoric System) tool detection device
 x1 CBN dressing unit with HF drive for automatic dressing of CBN grinding wheels (ceramic bond and synthetic resin)
 x1 T16 grinding turbine - speed: 160,000 rpm - reference: 164225
 x1 turbine support with filter for use with T10 and T16 turbines - reference: 166497
 x1 60S-TC grinding motor, speed 9000 - 60000 [rpm], for SK20 collets - part number: 208450
 x1 intermediate plate for aligning motors and turbines - reference: 192940
 x1 centring watch holder for grinding motor rotor - reference: 191790
 x15 wheel holder cleats
 x1 cable for grinding motor
 Various tools
 Full documentation

Seller:

ProdEq Trading GmbH
 Michael Weishaupt
 Reckholder 1, 9527 Niederhelfenschwil, Switzerland
 +41 71 948 70 60
 michael.weishaupt@prodeq.ch