

Data Sheet

Reference No.: 43505

Obdelovalni center - univerzalni (APC)

Brand: EXERON
Model: HSC MP7/5
YoM, approx.: 2016 used
Reconditioned:
Controls: CNC krmiljenje HEIDENHAIN TNC 640



Working Range -cubic-

number of processing axes (excl parallel axes):	5
X-axis travel:	640 mm
Y-axis travel:	250 mm
Z-axis travel:	400 mm
rotating range B-axis from:	105 °
rotating range B-axis up to:	-105 °
rotating range C-axis from:	0 °
rotating range C-axis up to:	360 °
razdalja pinola - vpenjalno ploskev (maks.):	450 mm

Table

workpiece load (max):	60 kg
-----------------------	-------

spindle / head

spindle revolutions (max):	42000 /min
----------------------------	------------

Tool magazine

number of positions:	90
----------------------	----

Electrical specifications

mains voltage:	400 V
mains frequency:	50 Hz

Dimensions / weights

space requirements -left/right-:	2400 mm
space requirements -front/back-:	2370 mm
total height:	3000 mm

attachments

band filtration unit: yes
through spindle coolant
attachment: yes
closed cabin: yes
European CE standards: yes

Additional Information:

Machine equipment: - Accuracy package - Workpiece magazine for 36 ITS pallets 50/148 - Renishaw OMP 400 (measuring probe)
- MHT media distributor table chuck PowerChuck P Ø150 Tool measurement BLUM Infrared probe
Renishaw OMP400 Medium distributor MHT with 3 dosing settings Thermal package / Accuracy package
Kinematic-Opt incl. calibration pallet ball 30mm
Dynamic Collision Controller (DCM) Z-axis compensation Fault indicator exo-call Remote diagnostics exo-net 1 network connection Hand control bar HSCI FS Additional light for working area Pressure amplification for chuck

Seller:

ProdEq Trading GmbH
Michael Weishaupt
Reckholder 1, 9527 Niederhelfenschwil, Switzerland
+41 71 948 70 60
michael.weishaupt@prodeq.ch

Photos & Documents

Reference No.: 43505

