

Data Sheet

Reference No.: 43619

Transferna stiskalnica - mehanska

Brand: KRUPP
 Model: PKZZ ST315
 YoM, approx.: 1981 used
 Reconditioned:
 Controls:



Press Design

drive system: eccentric / crank
 openings in uprights: yes
 feedstock transport direction: right to left

Press forces

total force (nominal): 315 to
 nominal work capacity: 45 kNm

Press Table

table surface (left-right): 2250 mm
 table surface (front-back): 1100 mm
 thickness of bolster plate: 150 mm
 height above floor level: 1000 mm

Slide

slide force: 315 to
 table surface (left-right): 2250 mm
 table surface (front-back): 880 mm
 stroke: 210 mm
 stroke rate (max.): 80 /min

slide (mechan. Press)

slide adjustment: 120 mm
 stroke rate (min.): 25 /min
 stroke rate (max.): 80 /min
 main drive power: 60 kW

slide ejector / cushion

working principle: pneumatical
 nominal force: 1.5 to
 stroke: 80 mm

Tool Assembly Dimensions

shut height (stroke down, adjustment up), BDC: 560 mm
 distance between columns (H-frame): 2250 mm
 passline opening (free passage in side columns): 800 mm

Coil Chair

coil weight max.: 3 to

Decoiler

design: single reel, traversable
 Sirina traku maks.: 400 mm
 coil weight max.: 3 to
 max. diameter of coil: 1500 mm
 mandrel expansion range from: 470 mm
 mandrel expansion range up to: 520 mm

Leveller Unit

Sirina traku maks.: 500 mm
 material cross section max. (450 N/mm²): 2000 mm²
 number of leveller rolls: 9
 diameter of leveller rolls: 60 mm
 number of infeed-/outfeed rolls: 2
 feed velocity min.: 40 m/min
 loop controls: yes

Strip-Feeder

Sirina traku maks.: 400 mm
 sheet thickness max.: 5 mm
 feeding step max.: 1300 mm

Dimensions / weights

height above floor level: 5000 mm
 total weight approx.: 44000 kg

Additional Information:

Transfer system SANDER Scrap conveyor Condition: Stand welded

Seller:

ProdEq Trading GmbH
 Frank Goedicke
 Reckholder 1, 9527 Niederhelfenschwil, Switzerland
 +41 71 948 70 60
 frank.goedicke@prodeq.ch

Photos & Documents

Reference No.: 43619

