

Data Sheet

Reference No.: 55439

Obdelovalni center - portalni, univerzalni

Brand: KAO MING
Model: KMC-1800 DV
YoM, approx.: 2002 used
Reconditioned:
Controls: CNC krmiljenje FANUC 18 M



Working Range -cubic-

number of processing axes (excl parallel axes):	3
.. among of them simultaneous CNC axes:	3
X-axis travel:	1940 mm
Y-axis travel:	1200 mm
Z-axis travel:	700 mm

Table

table surface (left-right):	1120 mm
table surface (front-back):	1800 mm
workpiece load (max):	3500 kg

spindle / head

spindle revolutions (min):	100 /min
spindle revolutions (max):	15000 /min
tool fixture: HSK E63	
vretena navor:	150 Nm

Axis drives

rapid traverse X:	30000 mm/min
rapid traverse Y:	40000 mm/min
rapid traverse Z:	24000 mm/min

Tool magazine

number of positions:	32
tool weight max.:	8 kg

Electrical specifications

mains voltage:	400 V
mains frequency:	50 Hz

Dimensions / weights

space requirements -left/right-:	5300 mm
space requirements -front/back-:	2600 mm
total height:	2800 mm
total weight approx.:	14500 kg

attachments

chip conveyor: yes
coolant unit: yes
band filtration unit: yes
closed cabin: yes

Additional Information:

Features:
- Grid panel 40/40 (1120x1800)
- Operating hours approx. 22,000h (20h/week)

Seller:

ProdEq Trading GmbH
Michael Weishaupt
Reckholder 1, 9527 Niederhelfenschwil, Switzerland
+41 71 948 70 60
michael.weishaupt@prodeq.ch

Photos & Documents

Reference No.: 55439

