

Tehnični list

Referenčna št.: 57108

Stiskalnica - mehanska

Proizvajalec: ZANI
Model: AF300 2MBT 18.20
Leto izdelave, pribl.: 1996 used
Obnovljeno:
Krmiljenje:



Press Design

drive system: eccentric / crank
openings in uprights: yes
number of slide actions: 2

Press forces

total force (nominal): 300 to

Slide

stroke: 200 mm
stroke rate (max.): 60 /min

slide (mechan. Press)

slide adjustment: 100 mm
stroke rate (min.): 20 /min
stroke rate (max.): 60 /min

Tool Assembly Dimensions

shut height (stroke down,
adjustment up), BDC: 800 mm

Electrical specifications

total power consumption: 35 kW
mains voltage: 380 V

Dimensions / weights

total weight approx.: 38000 kg

Attachments (presses)

European CE standards: yes

Additional Information:

Electrical panel renewed

Machine currently in working order, connected

Seller:

Post-Venta Carreras S.A.
Antonio Vega
Pol. Ind. Els Plans d'Arau C/ Nicolau Copèrnic, 2, 08787
La Pobla de Claramunt, Spain
+34 938 088 099
antonio@prodeq.es

Photos & Documents

Reference No.: 57108



ZANI 22078 TURATE (CO) ITALY Tel. (030) 02.56489355 Fax (39) 02.56489352		PRESSA MODELLO PRESSE MODELLE PRESSE MODEL AF 300.400Y 18.20	
MATRICOLA SERIAL NUMBER Nr. 96.1353		ANNO DI FABBRICAZIONE YEAR OF MANUFACTURE YEAR OF PRODUCTION CE 1996	
FORZA NOMINALE PRESSION RATED FORCE X COUPES STROKES	200	COUPES AL MINUTO COUPES PER MINUTE STROKES PER MIN.	40 3000
PRESSIONE COUPES PRESSURE COUPES PRESSURE FORCE STROKES		55 0	PESO RETTO APPROX. POUX NET APPROX. APPROX. NET WEIGHT 39000
COURSE COURSE STROKE	200	POTENZA ELETTRICA PUISSANCE ELECTRIQUE ELECTRIC POWER kW 38 38	TENSIONE VOLTAGE VOLTAGE 380-50 110-230V
COUPES AL MINUTO COUPES PER MINUTE STROKES PER MIN.	20 - 60	PRESS. AREA COMPRESSA PRESS. AREA COMPRESSE COUPES AIR PRESSURE Bar 05 6	PRESS. GL. COUPLER PRESS. EQUIVALENTS BALANCE CIL. PRESS. Bar 0.5 5
DISTANZA TAVOLA/ALZATA DIST. TABLE/ALZATEAU TABLE/RISE	800	PESO DI ANFRETTO POUX D'ANFRET STOP POSITION PAX PAX T.B.C.	VEL. MAX VOLANO VIT. MAX VOLANT MAX FLYWHEEL SPEED RPM 876
REGOL. VITE ALZATA REGLAGE COUPLER RAN ADJUSTMENT	100	MAX. INNESTI AL MIN. MAX. INSERTION BAR MIN. (COUPES SINGLE STROKES)	MAX. INNESTI AL MIN. MAX. INSERTION BAR MIN. (COUPES SINGLE STROKES)