

Tehnični list

Referenčna št.: 57152

Obdelovalni center za struženje in rezkanje

Proizvajalec: DOOSAN
Model: PUMA TT 1800 SY
Leto izdelave, pribl.: 2012 used
Obnovljeno:
Krmiljenje: CNC krmiljenje FANUC 31I MODEL A



basic functions

number of spindles:	2
number of turrets:	2
live positions: yes	
number of c-axes:	2
number of y-axes:	1

Working Range Turning

turning diameter (max):	230 mm
workpiece length max.:	700 mm

main spindle

spindle revolutions (min):	50 /min
spindle revolutions (max):	5000 /min
c-axis: yes	

counter spindle

spindle revolutions (min):	50 /min
spindle revolutions (max):	6000 /min
c-axis: yes	

X/Z slide

tool fixture: Turret

Electrical specifications

mains voltage:	400 V
mains frequency:	50 Hz

Dimensions / weights

space requirements -left/right-:	2800 mm
space requirements -front/back-:	1630 mm
total height:	2200 mm
total weight approx.:	9000 kg

attachments (turning)

chip conveyor: yes
coolant unit: yes
band filtration unit: yes
coolant through turret: yes
through spindle coolant
attachment: yes
hydraulic system: yes
European CE standards: yes

Additional Information:

Features:

- FMB turbo 8-80 bar feeder
- Y-axis in the upper turret

Seller:

ProdEq Trading GmbH
Michael Weishaupt
Rorschacher Str. 286, 9016 St Gallen, Switzerland
+41 71 948 70 60
michael.weishaupt@prodeq.ch

Photos & Documents

Reference No.: 57152

