ProdEq
www.prodeq.com

navigating Production Equipment
back into Work and Profit

Tehnični list

Referenčna št.: 57591

Obdelovalni center s pomičnim stebrom - univerzalni



Proizvajalec:	SORALUCE
Model:	SP 8000
Leto izdelave, pribl.:	1997 used
Obnovljeno:	
Krmiljenje:	CNC krmiljenje HEIDENHAIN TNC 530

Working Range -cubic-	
X-axis travel:	6500 mm
Y-axis travel:	1600 mm
Z-axis travel:	1200 mm

Table	
table surface (left-right):	8000 mm

spindle / head	
spindle revolutions (min):	30 /min
spindle revolutions (max):	3000 /min
tool fixture: ISO SK 50	

Axis drives	
traverse velocity X (max):	5000 mm/min
rapid traverse X:	15000 mm/min
rapid traverse Y:	15000 mm/min
rapid traverse Z:	15000 mm/min

Tool magazine	
magazin type: chain magazine	
number of positions:	40

Electrical specifications	
total power consumption:	22 kW
mains voltage:	400 V
mains frequency:	50 Hz

Dimensions / weights	
space requirements -left/right-:	11000 mm
space requirements -front/back-:	4455 mm
total height:	3850 mm
total weight approx.:	28000 kg

Seller:

ProdEq Trading GmbH
Michael Weishaupt
Rorschacher Str. 286, 9016 St Gallen, Switzerland
+41 71 948 70 60
michael.weishaupt@prodeq.ch

Photos & Documents

Reference No.: 57591









Schwenkkopf