ProdEq
www.prodeq.com

navigating Production Equipment
back into Work and Profit

Tehnični list

Referenčna št.: 57777

Obdelovalni center za struženje in rezkanje



Proizvajalec:	MORI SEIKI
Model:	MT 3000/1500
Leto izdelave, pribl.:	2005 used
Obnovljeno:	
Krmiljenje:	CNC krmiljenje MORI SEIKI MSG-501

basic functions

number of spindles:	1
live positions: yes	
number of c-axes:	1
number of y-axes:	1
number of b-axes:	1

Working Range Turning

swing diameter (max):	815 mm
turning diameter (max):	560 mm
worpiece length max.:	1500 mm

main spindle

spindle revolutions (max):	3000 /min
spindle bore diameter:	90 mm
c-axis: yes	

X/Z slide

Z-axis travel:	1595 mm
Y-axis travel:	220 mm
rotating range B-axis up to:	225 °
rapid traverse Z:	30000 mm/min
rapid traverse X:	24000 mm/min
rapid traverse Y:	24000 mm/min
tool fixture: Milling Spindle	
number of tool positions (total):	120
- rotation speeds (max):	8000 /min

tailstock

distance betw. centers (max):	1590 mm
sleeve stroke:	150 mm
sleeve diameter:	110 mm
taper: MK 5	
Z-axis travel:	1400 mm

Electrical specifications

mains power supply:	70 kVA
mains voltage:	400 V
mains frequency:	50 Hz

Dimensions / weights

space requirements -left/right-:	6400 mm
space requirements -front/back-:	3070 mm
total height:	3300 mm
total weight approx.:	18500 kg

attachments (turning)

tailstock: yes
chip conveyor: yes

Additional Information:

Features:
- Capto-C6 tool holder (120 tool positions)
- 400 mm diameter Forkhardt chuck
- Tool holder included

Machine still powered on

Seller:

ProdEq Trading GmbH
Michael Weishaupt
Rorschacher Str. 286, 9016 St Gallen, Switzerland
+41 71 948 70 60
michael.weishaupt@prodeq.ch

Photos & Documents

Reference No.: 57777





