

Data Sheet

Reference No.: 49648

presa za fino rezanje - mehanička

Brand: FEINTOOL
Model: GKP F 100/160
YoM, approx.: 1972 used
Reconditioned:
Controls:



Press Design

drive system: knuckle-joint
frame design: H-frame, monoblock

Slide

total force (nominal): 160 to
stroke: 60 mm
stroke rate (max.): 72 /min

Counter Ram

nominal force: 40 to
stroke: 60 mm

V-Ring

nominal force: 50 to
stroke: 13 mm

Tool Dimensions

lower table (left-right): 470 mm
lower table (front-back): 470 mm
upper table (left-right): 500 mm
upper table (front-back): 470 mm
shut height max.: 277 mm
ram adjustment: 80 mm
distance between columns (H-frame): 500 mm
passline opening (free passage in side columns): 220 mm

Strip-Feeder

feeder type: roll feeder
sheet width max.: 210 mm
sheet thickness max.: 6 mm
feeding step max.: 180 mm

Electrical specifications

mains voltage: 380 V
mains frequency: 50 Hz

Dimensions / weights

space requirements -left/right-: 1950 mm
space requirements -front/back-: 1800 mm
total height: 2850 mm
total weight approx.: 9000 kg

Seller:

Post-Venta Carreras S.A.
Eduard Peña
Pol. Ind. Els Plans d'Arau C/ Nicolau Copèrnic, 2, 08787
La Pobla de Claramunt, Spain
+34 938 088 099
edu@prodeq.es

Photos & Documents

Reference No.: 49648

